





# ADDITIONAL PRODUCT INFORMATION

		<b>Recommendation for standard applications</b>			
<b>Floor covering</b>		<b>EGGER Design GreenTec</b>			
<b>Bonding</b>	Adhesive	<b>SikaBond®-151</b>	<b>SikaBond® AT-80N (CH)</b>	<b>SikaBond®-54 Parquet</b>	
	Toothing	Depending on the condition of the substrate TKB B3 or B6			
	Consumption	600 – 950 g/m <sup>2</sup>			
<b>Sealing</b>	Waterproofing membrane				
	Adhesive				
	Toothing				
	Consumption				
<b>Leveling</b>	Leveling compound if flatness acc. DIN18202 resp. SIA 414/2 is not given	<b>Sikafloor®-400 Level</b>	<b>Sikafloor®-400 Level AT (CH)</b>	<b>Sikafloor®-4020 FiberLevel (CH)</b>	
	Consumption	approx. 1,5 kg/m <sup>2</sup>	approx. 1,5 kg/m <sup>2</sup> /mm	approx. 1,6 kg/m <sup>2</sup> /mm	
<b>Priming</b>	Priming before levelling	<b>Sikafloor®-01 Primer</b> (1:1 – 1:3 mixed with water)		<b>Sikafloor®-02 Primer</b>	
	Consumption	approx. 70 g/m <sup>2</sup>		approx. 120 g/m <sup>2</sup>	
	Priming before installation	<b>Sika® Primer MB</b>	<b>Sika® Primer MB Rapid</b>	<b>Sika® Primer MR Fast</b>	
	Consumption	approx. 250 g/m <sup>2</sup> per roll layer	approx. 100 – 150g/m <sup>2</sup> per roll layer	approx. 100 – 150g/m <sup>2</sup> per roll layer	
<b>Preparation</b>	Preparation according to DIN 18356 or SIA 253 e.g. cleaning, sanding, vacuuming etc.				
<b>Substrate</b>	Concrete	Cementitious screed	Calcium sulphate / Anhydride screed	Existing ceramic tiles	Mastic asphalt

 <b>BUILDING TRUST</b>		<b>Recommendation for wet room (bathroom) application</b>			
<b>Floor covering</b>		<b>EGGER Design GreenTec</b>			
<b>Bonding</b>	Adhesive	<b>SikaBond®-151</b>	<b>SikaBond® AT-80N (CH)</b>	<b>SikaBond®-54 Parquet</b>	
	Toothing	Depending on the condition of the substrate TKB B3 or B6			
	Consumption	600 – 950 g/m <sup>2</sup>			
<b>Sealing</b>	Waterproofing membrane	<b>If needed, please obtain technical information in advance</b>			
	Adhesive				
	Toothing				
	Consumption				
<b>Leveling</b>	Leveling compound if flatness acc. DIN18202 resp. SIA 414/2 is not given	<b>Sikafloor®-400 Level</b>	<b>Sikafloor®-400 Level AT (CH)</b>	<b>Sikafloor®-4020 FiberLevel (CH)</b>	
	Consumption	approx. 1,5 kg/m <sup>2</sup>	approx. 1,5 kg/m <sup>2</sup> /mm	approx. 1,6 kg/m <sup>2</sup> /mm	
<b>Priming</b>	Priming before levelling	<b>Sikafloor®-01 Primer (1:1 – 1:3 mixed with water)</b>		<b>Sikafloor®-02 Primer</b>	
	Consumption	approx. 70 g/m <sup>2</sup>		approx. 120 g/m <sup>2</sup>	
	Priming before installation	<b>Sika® Primer MB</b>	<b>Sika® Primer MB Rapid</b>	<b>Sika® Primer MR Fast</b>	
	Consumption	approx. 250 g/m <sup>2</sup> per roll layer	approx. 100 – 150g/m <sup>2</sup> per roll layer	approx. 100 – 150g/m <sup>2</sup> per roll layer	
<b>Preparation</b>	Preparation according to DIN 18356 or SIA 253 e.g. cleaning, sanding, vacuuming etc.				
<b>Substrate</b>	Concrete	Cementitious screed	Calcium sulphate / Anhydride screed	Existing ceramic tiles	Mastic asphalt

## LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

**Sika Services AG**  
Corp. TM Sealing & Bonding  
Tüffenwies 16  
8048 Zürich  
Switzerland  
[www.sika.com](http://www.sika.com)

API – Additional Product Information EGGER Design    Deutsch  
GreenTec

09.06.2020 Version 1

